

# CD600 PCB

## Technical specifications



Process chamber	<p><u>Material:</u> aluminium <u>Inside dimensions:</u> 600 x 600 x 600 mm <u>Volume:</u> 216 liter <u>Loading:</u> max 7 rigid boards, dimensions 520 x 450 mm</p>
Vacuum measurement	Baratron gauge
Generator	2000 W kHz
Pumping system	Rotary vane roughing pump group
PLC	<p>The equipment and automatic processing is fully controlled by an industrial PLC. The HMI (user interface) runs over an industrial touch panel PC having following properties:</p> <ul style="list-style-type: none"><li>• 17" touch screen.</li><li>• LED backlight.</li><li>• Integrated SSD hard drive.</li></ul> <p>The HMI offers following functionalities:</p> <ul style="list-style-type: none"><li>• Process &amp; Instrumentation Diagram showing real-time machine status.</li><li>• User-level based log on for managing user rights from operator to engineer mode.</li><li>• Recipe management system offering unlimited number of recipes, each recipe representing a unique set of process parameters.</li><li>• Diagnostic functions.</li><li>• Alarm management.</li><li>• Optional historical data logging and viewing.</li></ul>
Electricity	380V AC, 50Hz, 40A
Process gas	1 gas line with MFC (Mass Flow Controller)
Safety features	Emergency-off-switch, vacuum interlock, over temperature interlock, CE-label
Process gas connection	¼"-Swagelok-fitting, input pressure 1 Bar

Options: data logging, additional gas channels, dry pump group, customised loading

